SAFETY DATA SHEET

www.zettex.com

according to 1907/2006/EC, Article 31

Printing date: 18.04.2019

Version: 10

Page 1/10 Revision: 18.04.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking • 1.1 Product identifier • Trade name: Zettex Balsem • Article number: • 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. • Application of the substance / the mixture Lubricant • 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier: Zettex Europe BV Plaza 20, 4782 SK Moerdijk The Netherlands +31(0)888-938839 info@zettex.nl

• 1.4 Emergency telephone number: Zettex Europe BV 031 (0) 888 938 839 (Mon-Fri 09:00-17:00)

SECTION 2: Hazards identification

 \cdot 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

GHS02 flame

www.zettex.nl

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

GHS07	
Skin Irrit. 2 H315	Causes skin irritation.
Eye Irrit. 2 H319	Causes serious eye irritation.
Asp. Tox. 1 H304	May be fatal if swallowed and enters airways.

· 2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons,C10-C13,n-alkanes,cyclic,<2%aromates, Benzene <0.1% alpha-Pinene Terpinolene p-cymene • Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Printing date: 18.04.2019

Version: 10

Revision: 18.04.2019

Trade name: Zettex Balsem

	(Contd. of page 1)				
 Precautionary st 	tatements				
P101	If medical advice is needed, have product container or label at hand.				
P102	Keep out of reach of children.				
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.				
P211	Do not spray on an open flame or other ignition source.				
P251	Do not pierce or burn, even after use.				
P264	Wash thoroughly after handling.				
P280	Wear protective gloves / eye protection / face protection.				
P302+P352	IF ON SKIN: Wash with plenty of water.				
P321	Specific treatment (see on this label).				
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lense					
	present and easy to do. Continue rinsing.				
P332+P313	If skin irritation occurs: Get medical advice/attention.				
P362+P364	Take off contaminated clothing and wash it before reuse.				
P337+P313	If eye irritation persists: Get medical advice/attention.				
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.				
• Additional infor	mation:				
EUH208 Contains Coumarin. May produce an allergic reaction.					
Buildup of explos	Buildup of explosive mixtures possible without sufficient ventilation.				
· 2.3 Other hazar	· 2.3 Other hazards				
· Results of PBT and vPvB assessment					
• PBT : Not applica	able				

- **PBT:** Not applicable.
- **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

*

• **Description:** Active substance with propellant

-
 Dangerous components:

Dangerous components:		
CAS: 1174522-09-8 EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons,C10-C13,n-alkanes,cyclic,<2%aromates, Benzene <0.1% Asp. Tox. 1, H304	50-<75%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-<10%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	1-<2.5%
CAS: 68308-64-5 EINECS: 269-662-8	Quaternary ammonium compounds, cocoalkylethyldimethyl, Et sulfates Skin Corr. 1A, H314; Aquatic Acute 1, H400; Acute Tox. 4, H302	≥0.25-<1%
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38	butanol Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	0.1-<1%
· Ingredients according to de	etergents guidline 648/2004/EC	
aliphatic hydrocarbons		≥30%
)(Contd. on page

GB -

Printing date: 18.04.2019

Version: 10

Revision: 18.04.2019

Trade name: Zettex Balsem

perfumes (COUMARIN, COUMARIN), EUGENOL, Dihydroterpinyl acetate, alpha-Pinene

(Contd. of page 2) <5%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; call for medical help immediately.
- \cdot 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- Water haze Fire-extinguishing powder
- Carbon dioxide
- Alcohol resistant foam
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

- \cdot 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water. • 6.3 Methods and material for containment and cleaning up:
- Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

GB

Printing date: 18.04.2019

*

Version: 10

Revision: 18.04.2019

Trade name: Zettex Balsem

			(Contd. of page 3)
· 7.2 Condi	tions for safe storage, inclu	ding any incompatibilities	(contait of page b)
· Storage:			
	ents to be met by storeroor cool location.	ns and receptacles:	
		packagings with pressurised containers.	
	on about storage in one co		
		packagings with pressurised containers.	
	nformation about storage c ool, dry conditions in well sea		
	om heat and direct sunlight.	areu receptacies.	
7.3 Specif	ic end use(s) No further rele	vant information available.	
SECTIO	DN 8: Exposure contro	ls/nersonal protection	
		of technical facilities: No further data; see item 7.	
	ol parameters	or technical facilities: No further data, see item 7.	
		uire monitoring at the workplace:	
		3,n-alkanes,cyclic,<2% aromates, Benzene <0.1%	
	rt-term value: 1200 mg/m ³ , 1		
	butane (containing < 0.1%)	**	
	rt-term value: 1810 mg/m ³ , 7		
	g-term value: 1450 mg/m ³ , 6		
	c (if more than 0.1% of buta-	-1.3-diene)	
74-98-6 pi	=		
	g-term value: 1800 mg/m ³		
	obutane (containing < 0,1 4	‰ butadiene (203-450-8))	
	rt-term value: 2400 mg/m ³ g-term value: 1900 mg/m ³		
67-63-0 р	ropan-2-ol		
	rt-term value: 1250 mg/m ³ , 5		
	g-term value: 999 mg/m ³ , 40	0 ppm	
71-36-3 bi			
WEL Sho Sk	rt-term value: 154 mg/m ³ , 50) ppm	
DNELs			
67-63-0 р	ropan-2-ol		
Oral	DNEL Long term-systemic	26 mg/kg bw/day (Consumer)	
Dermal	DNEL Long term-systemic	319 mg/kg bw/day (Consumer)	
		888 mg/kg bw/day (Worker)	
Inhalative	DNEL Long term-systemic	89 mg/m3 (Consumer)	
		500 mg/m3 (Worker)	
Additiona	l information: The lists vali	d during the making were used as basis.	
· 8.2 Expos	ure controls		
	protective equipment:		
	rotective and hygienic means the before breaks and at the end		
	ale gases / fumes / aerosols.	a of work.	
Respirato	ry protection:		
Filter A/P2		ice in case of insufficient ventilation	
Use suitab Filter A2P		ice in case of insufficient ventilation.	
	-		(Contd. on page 5)

(Contd. on page 5)

_____ GB -

Printing date: 18.04.2019

Version: 10

Revision: 18.04.2019

Trade name: Zettex Balsem

(Contd. of page 4) · Protection of hands: Wear gloves for the protection against chemicals according to EN 374 Protective gloves Solvent resistant gloves Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.5 mm Penetration time of glove material For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made. The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Safety glasses Tightly sealed goggles • Body protection: Use protective suit. (EN-13034/6) **SECTION 9: Physical and chemical properties** · 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: Aerosol **Colour:** Not determined. · Odour: Characteristic · Odour threshold: Not determined. · pH-value: Not determined. Change in condition Molting point/fne oging noint Undatarminad

Melting point/freezing point: Initial boiling point and boiling	range: -44.5 °C
· Flash point:	-97 °C
· Flammability (solid, gas):	Not applicable.
• Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible. Not determined.
	(Contd. on page 6

- GB

Printing date: 18.04.2019 Version: 10 Revision: 18.04.2019

Trade name: Zettex Balsem

	(Contd. of pa
Explosion limits:	
Lower:	0.7 Vol %
Upper:	12 Vol %
Vapour pressure at 20 °C:	2100 hPa
Density at 20 °C:	0.71 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	93.9 %
Solids content:	100.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1174522-0	9-8 Hydr	ocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%	
Oral	LD50	>5000 mg/kg (rat)	
Dermal	LD50	>5000 mg/kg (rabbit)	
Inhalative	LC50/4h	>4951 mg/l (rat)	
67-63-0 pi	67-63-0 propan-2-ol		
Oral	LD50	5840 mg/kg (rat)	
Dermal	LD50	13900 mg/kg (rabbit)	
Inhalative	LC50/6h	25000 mg/m3 (rat)	
 Primary irritant effect: Skin corrosion/irritation Causes skin irritation. Serious eye damage/irritation Causes serious eye irritation. Respiratory or skin sensitisation Based on available data, the classification criteria are not met. (Contd. on page 7) 			

Printing date: 18.04.2019

Version: 10

Revision: 18.04.2019

Trade name: Zettex Balsem

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

An	natic	toxicity:
		comercy

1174522-09-8 Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%

EL0(72h)	1000 mg/l (Pseudokirchneriella subcapitata	a)

LL0(96h) 1000 mg/l (Oncorhynchus mykiss (96h))

67-63-0 propan-2-ol

LOEC (8 days) 1000 mg/l (algae)

LC30/96n 9640 mg/l (Pimephales prometas	LC50/96h	9640 mg/l (Pimephales promelas)
---	----------	---------------------------------

LC50 (24h) 9714 mg/l (Daphnia magna)

• 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Harmful to aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB**: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
14.1 UN-Number		
ADR, ADN, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR, ADN	UN1950 AEROSOLS	
IMDG	AEROSOLS	

(Contd. of page 6)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date: 18.04.2019

Version: 10

Revision: 18.04.2019

Trade name: Zettex Balsem

	(Contd. of page
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class Label	2 5F Gases. 2.1
ADN ADN/R Class:	2 5F
IMDG, IATA	
Class	2.1
Label	2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Code	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
Transport category Tunnel restriction code	2 D
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
	(Contd. on page

Printing date: 18.04.2019

Version: 10

Revision: 18.04.2019

Trade name: Zettex Balsem

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements $150\ t$
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:

Class Share in %

NK 75-<100

- · VOC-CH 93.91 %
- · VOC-EU 666.7 g/l
- · Danish MAL Code 4-1
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- · Contact:

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
- DNEL: Derived No-Effect Level (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1
- Aerosol 1: Aerosols Category 1
- Press. Gas (Comp.): Gases under pressure Compressed gas
- Flam. Liq. 2: Flammable liquids Category 2

(Contd. on page 10)

(Contd. of page 8)

Printing date: 18.04.2019

Version: 10

Revision: 18.04.2019

Trade name: Zettex Balsem

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 (Contd. of page 9)

GB