

# Freeze Spray



## pin-pointed chilling down to -45°C

Freeze-Spray has many uses and is suitable for fault-finding in electronics and for repair works in industrial sector.

Freeze Spray quickly cools parts down to -45°C and allows pinpointed chilling of even the smallest construction parts.

Freeze Spray is non-conductive and neutral to materials (with the exception of plastic) and can be used in many industrial and technical applications.

## Technical Data

Odour	almost odourless
Features	targeted cooling down to -45°C
Storage stability	24 months

## Processing

Freeze Spray contains a special refrigerating agent for all application ranges. A local freezing of the sprayed area of up to -45°C can be produced. Freeze Spray immediately has a cooling effect without leaving any residues. Caution: Danger of hypothermia if contact with skin! Hold can strictly upright, do not shake can. Press spray top in short intervals as required. When using on electric appliances ensure good aeration before restoring power to avoid possible deflagration of gas nests by spark discharge.

## Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50°C.

## Safety and health

When using products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets must be observed.

## Technotopogs FZCO

Head Office Middle East: Hamriya Free Zone-Sharjah, UAE  
Tel: +971 6 5262004 • Fax: +971 6 5262030  
info@technotopogs.com • www.technotopogs.com

Westhafenplatz 1  
60327 Frankfurt/Main, Germany  
Tel: +49 (0) 69 710456072