

Leak Detection Spray



**Non flammable
anticorrosive
foam-forming leak detector according to DIN EN 14291**

Leak Detection Spray is non-flammable, anti-corrosive. The spray is used for the fast, convenient and reliable location of leaks (cracks or porous spots) in pressurized pipes.

Leak Detection Spray does not form any hazardous compounds with carbon dioxide (CO₂), propane, butane, acetylene, oxygen, city or natural gases.

Leak Detection Spray can be used wherever compressed air, natural or liquid gas is processed, and wherever leaky points can occur on fittings, threaded joints, and connections. It greatly contributes to the safety of pneumatic brakes and gas lines.

Technical Data

Odour	almost odourless
Features	approved for gas piping by German DVGW, suitable for oxygen and CO ₂
Storage stability	24 months
Colour	milky
Temperature resistance	0 to +50 °C

Processing

Spray on area to be tested. Bubbles will be formed if there is a leakage. Thanks to its high sensitivity even smallest leakages can be detected.

Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50°C.

Safety and health

When using products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets must be observed.

Technotopogs FZCO

Head Office Middle East: Hamriya Free Zone-Sharjah, UAE
Tel: +971 6 5262004 • Fax: +971 6 5262030
info@technotopogs.com • www.technotopogs.com

Westhafenplatz 1
60327 Frankfurt/Main, Germany
Tel: +49 (0) 69 710456072